


SYMBOL	TYPE	PRODUCT NAME	CONTACT NAME / NUMBER
		LED HIGH BAY	



SPECIFICATIONS	DESCRIPTION
OPERATING VOLTAGE : 90-305VAC, 50-60Hz	HIGH GRADE ALUMINIUM CONTROL GEAR EXCELLENT HEAT CONDUCTION PERFORMANCE FORMED BY THIN ALUMINIUM SHEET.
LED POWER : 80 W	
SYSTEM POWER : 90W	
OPERATING TEMPERATURE : -40°C TO +50°C	
CCT : 3000K-7000K	
LUMINOUS FLUX : 9500 lm	
LED LUMINOUS EFFICIENCY : 118 lm/W	
LIFESPAN : 50,000 HOURS	
CRI : Ra>70 (>70 OPTIONAL)	
OPTIONAL BEAM ANGLE : PC 80°/100°/120°	
IP PROTECTION : IP40 & IP65	INSTALLATION
WEIGHT : 5.6kg	SURFACE MOUNTED
	STANDARD
	TIS. 1955-2551

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	L	W	φ	
DLED-HB145-4080	80W.	LED	561	300	395	-