


SYMBOL	TYPE	PRODUCT NAME	CONTACT NAME / NUMBER
		FLUORESCENT (Insect Proof)	



<b>HOUSING</b>			<b>WIRING CABLE</b>			
HIGH GRADE DIE-FORM STEEL SHEET. SIX-STAGES ZINC-PHOSPHATE PRE-TREATMENT FOR RUST RESISTANT , FINISHED WITH WHITE POLTESTER POWDER BY ELECTROSTATIC METHOD TWO STAGES AND BAKED ENAMEL . THICKNESS <input type="checkbox"/> 0.6 mm , <input type="checkbox"/> 0.8 mm			THW 1x1.0 SQ.MM. 70 °C WIRING CABLE (STANDARD)			
<b>DIFFUSER</b>			<b>LOUVER</b>			
MADE FROM PRISMATIC ACRYLIC SHEET, DIE-FORM IN CRUVE SHAPE			NONE			
<b>REFLECTOR</b>			<b>LAMP AND HOLDER</b>			
NONE			G10q LAMP HOLDER			
<b>STANDARD</b>			<b>INSTALLATION</b>			
TIS.902 เล่ม 2 (1) - 2557 WITH CLASS I AND F MARK TIS.1955-2551			SURFACE MOUNTED			
MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
DLCL-101/32	32W	G10q	400	400	90	